

Amendments To the Claims:

Please amend the claims as shown.

1. (currently amended) A method for regulating a jitter buffer for buffering a data packet stream comprising:

- registering a transmission delay due to buffering for the data packets of the data packet stream;
- continuously deriving weighted mean delay values from registered transmission delays, wherein a shorter transmission delay is weighted higher than a longer transmission delay; and
- regulating a read-out speed of the jitter buffer as a function of the continuously derived weighted mean delay values so that said values are adjusted as a regulating variable to a predefined desired delay;
- comparing a currently registered transmission delay with a previously derived weighted mean delay value;
- determining a weighting of the currently registered transmission delay as a function of a result of the comparing, wherein the currently registered transmission delay is weighted with a first predefined weight value if the currently registered transmission delay is shorter than the previously derived weighted mean delay value and is weighted with a second predefined weight value if the currently registered transmission delay is longer than the previously derived weighted mean delay value, with the first weight value being larger than the second weight value, and further wherein a quotient of the first predefined weight value and the second predefined weight value is selected to reduce a data ~~packet~~packet loss rate.

2. (previously presented) A method according to Claim 1, wherein a new weighted mean delay value is derived from a previously derived weighted mean delay value and a currently registered transmission delay.

3-4. (cancelled)

5. (previously presented) A method according to Claim 1,
wherein the regulating variable is regulated by a single regulating circuit.
6. (currently amended) A jitter buffer regulating circuit for regulating a jitter buffer for buffering a data packet stream comprising:
- a registration device for registering a transmission delay due to buffering of a respective data packet of the data packet stream;
 - a mean-forming device for continuously deriving weighted mean delay values from registered transmission delays, with higher weighting of a shorter transmission delay compared to a higher transmission delay; and
 - a regulating device for adjusting the continuously derived weighted mean delay values to a predefined desired delay by regulating a read-out speed of the jitter buffer as a function of the continuously derived weighted mean delay values,
- wherein a currently registered transmission delay is compared with a previously derived weighted mean delay value, and the weighting of the currently registered transmission delay is determined as a function of the result of the comparison,
- wherein the currently registered transmission delay is weighted with a first predefined weight value if the currently registered transmission delay is shorter than the previously derived weighted mean delay value and is weighted with a second predefined weight value if the currently registered transmission delay is longer than the previously derived weighted mean delay value, with the first weight value being larger than the second weight value, and
- wherein a quotient of the first predefined weight value and the second predefined weight value is selected to reduce a data ~~packet~~packet loss rate.
7. (previously presented) A method according to Claim 2, wherein a currently registered transmission delay is compared with a previously derived weighted mean delay value, and the weighting of the currently registered transmission delay is determined as a function of the result of the comparison.

Serial No. 10/800,209
Atty. Doc. No. 2003P03809US

8. (previously presented) A method according to Claim 2, wherein the regulating variable is regulated by a single regulating circuit.

9-10. (cancelled)